

Ciao

6÷24 l - 1,1 kW



OILLESS








Ciao 25/1850

Ciao 6/1850

Comandati tramite pressostato elettromeccanico, gruppo accessori con manometro e rubinetto rapido universale. Protezione da sovraccarico del motore elettrico.

They are commanded by electro-mechanical pressure switch, an accessory unit with manometer and a universal quick coupler. The electric motor features overload protection.

Die Steuerung erfolgt durch einen elektromechanischen Druckschalter, eine Zubehörereinheit mit Manometer und einer Schnelltrennkupplung. Der Elektromotor besitzt einen Überlastschutz.

Codice Code	Prodotto Product	 L x D x H (cm)	 kg	 lbs	 tot.	 2 010000 036495
FOBB304FNM003	Ciao 6/1850	36 x 26 x 51	12,5	27,5	24	8017750219103
F0CC304FNM005	Ciao 25/1850	60,5 x 24 x 56,5	20,5	45,1	18	8017750214856

 l	Codice Code	Prodotto Product	 Volt/Ph	 kW	 HP	 Model	 l/min.	 m ³ /h	 c.f.m.	 bar	 p.s.i.	 R.P.M.	 n°	 n°	 dB(A)	 LwA	 L x D x H (cm)	 kg	 lbs
---	----------------	---------------------	--	---	---	--	---	--	---	--	--	---	---	---	--	--	---	---	--

SENZA OLIO MONOFASE 8 BAR | OILLESS SINGLE-PHASE 8 BAR | ÖLFREI EINPHASIG 8 BAR

6	FOBB304FNM003	Ciao 6/1850	230/1	1,1	1,5	OL1850	179	10,7	6,3	8	116	2850	1	1	80	95	33 x 25,5 x 50	11,5	25,4
24	F0CC304FNM005	Ciao 25/1850	230/1	1,1	1,5	OL1850	179	10,7	6,3	8	116	2850	1	1	80	95	58 x 27 x 60	19	41,9